

**ZONE 1/21
CL I / DIV 1**



i.safe MOBILE

IS530.1

**Always a step ahead!
The smart and innovative
Zone 1/CI I Div1-smartphone
with the most advanced
technology:**

**First Bluetooth® 5 industrial
smartphone with multifunc-
tional ISM interface, a huge
internal memory 64 GB and
the highest camera resolution
of its class.**



➤ Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ➤ © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1029MD01REV10_EN_05.2021

TECHNICAL FEATURES



ATEX approval:
EX-Zone 1/21
Ⓜ II 2G Ex ib IIC T4 Gb
Ⓜ II 2D Ex ib IIC T135°C
Db IP6X



IECEx approval:
EX-Zone 1/21
Ex ib IIC T4 Gb
Ex ib IIC T135°C Db IP6X



NEC500 approval:
Class I, II, III Division 1
Groups A B C D E F G, T4
Intrinsically Safe



EAC approval:
1Ex ib IIC T4 Gb X
Ex ib IIC T135°C Db X IP64



2,4 GHz + 5 GHz: IEEE
802.11a/ b/g/n/ac/e/k/r/h
with max. 8 connections
hotspot



GSM 850/900/1800/
1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-FDD: B1/2/3/4/5/7/8/12
with MFBI B13/14/17/20/25/
26/28A/28B/29/30/66
LTE-TDD: B38/B39/B40/B41
TD-SCDMA: B34/B39



Android™ 10



Size: 155 x 80 x 25 mm,
weight: 325 g



Bluetooth® 5



2 cameras: 13 MP AF
rear camera and 5 MP
front camera



Qualcomm Snapdragon
SDM660 Octa-Core
Kryo Gold-Quad cores
2,2 GHz
Kryo Silver-Quad cores
1,8 GHz
4 GB RAM
64 GB internal memory



External memory
microSD up to 128 GB



Near Field
Communication



Dual micro-SIM



Universal, lateral
ISM interface



SOS key
Loneworker protection
LWP ready (third party
application required,
based on country
specific regulations)

FURTHER FEATURES



Waterproof: 1 hour
up to 2 m, impervious to
dust and microparticles



Operation range from
-20 °C to 60 °C



Drop-protection,
tested against: vibrations,
shock and extreme
temperatures.



4,5" Gorilla Glass®
3. generation,
resolution 854 x 480 pixel



Usable with gloves



Amplified loudspeaker



3600 mAh Battery,
replaceable,
3,8 V; 13,68 Wh



GPS, A-GPS, Glonass,
Beidou, Galileo



Gyroscope, acceleration,
magnetic- and proximity
sensor



Magnetic charging port

SET CONTENT

Smartphone, Battery, Adapter, i.safe PROTECTOR 2.0 Type C USB Cable,
i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Screwdriver, Quick Start
Manual and Safety Instructions